



Turn to the Experts.™

# BACview<sup>6</sup>

## Part Numbers: BACVIEW6 & BV6H

Locally access Open controllers with the easy-to-use BACview<sup>6</sup> keypad/display. The BACview<sup>6</sup> serves as a configuration tool for Open controllers, and can be used to monitor, control, and configure the attached Carrier equipment. The BACview<sup>6</sup> features a numeric keypad, directional keys, and four programmable function keys. A large 4-line by 40-character backlit LCD display is provided for easy reading, even in poor lighting conditions.

The BACview<sup>6</sup> can be ordered as a factory-installed option on Carrier equipment, or it can be field-installed on Carrier equipment (BACVIEW6). It is also available as a portable commissioning tool (BV6H). All BACview versions includes an alarm indicator light and an audible warning to alert you during alarm conditions. The BACview<sup>6</sup> Handheld includes a padded backing, rugged design, and a 6 foot cable that attaches to the Open controller, providing technicians with a powerful and mobile tool for commissioning, troubleshooting, and maintenance.



### Key Features and Benefits

- Plugs directly into Open controller using attached cable. Or, for added convenience, plugs directly into a SPT sensor located in the controlled space.
- Provides simple access to setpoints, time schedules, status values, unit configuration parameters, and alarm history.
- Find relevant information quickly with simple and intuitive navigation screens.
- Keeps equipment secure with 3 security levels and built-in password protection.

### Specifications

Power	Supplied by the Rnet port through the included cable (+12Vdc @ 250mA)
Physical	Rugged aluminum enclosure and heavy-duty rubber backing for protection
Operating Range	32° to 120°F (0.0° to 48.9°C), 10%-90% RH non-condensing
Backlit LCD Display	4-line by 40-character display
Hardware Compatibility	All Open controllers with built-in BACview screens
Status Indication	Alarm LED indicator and audible horn when alarm conditions are present
Protection	Provides 15KVESD protection to the enclosure
Listed by:	UL 916 (PAZX), CE (1997), FCC Part 15 - Subpart B - Class A
Weight	1.5 lbs. (.68 Kg)
Overall Dimensions	9-5/8" (width) by 4-15/16" (height) by 1" 245mm (width) by 125mm (height) by 25mm

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs, without notice or without incurring obligations.

CARRIER CORPORATION ©2009

A member of the United Technologies Corporation family. Stock symbol UTX. 11-808-406-01 Rev. 05/09

[www.carrier.com](http://www.carrier.com)  
1-800-CARRIER