



Note)

- 1) Heat insulation material : fiber glass, non-asbestos or similar material.
- 2) Total heating/cooling insulation areas includes the machine pipe area.
- 3) The machine has a primary coat of corrosion-inhibiting paint ex-works.
(does not include finish coat)
- 4) Always use non-combusible insulation material.
- 5) Do not insulate the refrigerant pump motor and sight glass.
- 6) The evaporator and chamber covers need to be opened for maintenance. This should be taken into account when completing the insulation work.

Model	Hot surface			Cold surface	
	100mm	75mm	30mm	50mm	30mm
16DJ-11	5.8	2.2	2.9	4.0	0.4
16DJ-12	6.2	2.2	3.0	4.0	0.4
16DJ-13	7.8	3.2	4.2	5.5	0.4
16DJ-14	8.0	3.2	4.3	5.5	0.4
16DJ-21	10.1	3.8	4.9	6.1	0.5
16DJ-22	10.4	3.8	5.0	6.1	0.5
16DJ-23	11.8	4.8	5.5	7.8	0.5
16DJ-24	12.5	4.8	5.6	7.8	0.5
16DJ-31	14.5	5.5	6.2	8.5	0.7
16DJ-32	15.2	5.5	6.4	8.5	0.7
16DJ-41	17.5	5.7	6.8	9.9	0.7
16DJ-42	18.1	5.7	7.0	9.9	0.7

Model	Hot surface			Cold surface	
	100mm	75mm	30mm	50mm	30mm
16DJ-51	19.6	5.4	7.6	13.8	1.1
16DJ-52	20.7	5.9	7.9	15.0	1.1
16DJ-53	21.7	6.2	8.2	16.1	1.1
16DJ-61	25.4	7.2	9.7	17.5	1.2
16DJ-62	27.2	7.7	10.1	18.7	1.2
16DJ-63	28.9	8.2	10.5	20.0	1.2
16DJ-71	35.4	10.4	12.1	10.9	1.4
16DJ-72	37.4	10.7	12.4	11.4	1.4
16DJ-73	39.4	11.0	12.7	11.8	1.4
16DJ-81	42.5	11.0	13.0	13.1	1.5
16DJ-82	44.0	11.3	13.5	13.6	1.5



Insulation area

Model

TSA-16DJ

Drawing code

CM-016-001-01-0